# Weller®



# WT1011M

1 CHANNEL NANO/PICO SOLDERING KIT, 95 W, 120 V

ORDER NO: WT1011M

## COMPACT, POWERFUL, VERSATILE.

#### BOOST YOUR PRODUCTIVITY

#### Discover the WT 1M Soldering Station, your ultimate productivity partner.

With extremely fast heat-up and recovery times, it handles all tasks effortlessly. No more juggling tools or compromising performance – just reliable versatility and unmatched value. Choose worry-free precision and unstoppable productivity.



#### > 1 CHANNEL NANO/PICO SOLDERING KIT (95 W)

to cover smallest soldering tasks including WTPP MS Nano/Pico pencil with active (cartridge) tip technology

#### > RTPTIP FAMILY

with 3 seconds heat-up timeHigh productivity

#### > HIGH PRODUCTIVITY

#### > INTUITIVE USE

thanks to clear menu structure

#### > REDUCED FOOTPRINT

thanks to stackability

#### > GRAPHICAL BACKLIT LC-DISPLAY

#### > HIGH PERFORMANCE AND FUNCTIONALITY many connectable tools

#### > HOUSING COVER

useable as storage

#### > OFF TIME, PROCESS WINDOW, Lock function, Offset

#### > STACKABLE UNITS

useable as storage

#### > CONNECTABLE TO

ZeroSmog Fume Extraction Units





# #PowerfulTogether

#### weller-tools.com



Choose Weller WT Soldering Stations.

#### SCOPE OF SUPPLY

WT1M Power Unit, 120V WTPP MS Soldering Iron, 40 W, 12 V RTP 004 S MS Nano/Pico Soldering Tip WSR 205 Safety Rest with Stop & Go Function

#### **TECHNICAL DATA SOLDERING STATION WT1M**

**Dimensions L x W x H (mm)** 150 x 130 x 101 **Dimensions L x W x H (inch)** 5.91 x 5.12 x 3.98

Fuse 120V (mA) T500

Weight approx. (kg) 1,9

Mains supply voltage (V/Hz)

120 / 50 120 / 60 100 / 50/60

Power consumption (W) 95

Safety class I. antistatic housing III, Soldering tool

Temperature range / Tool dependent °F 150-850 / 950

Temperature accuracy (°C/°F)  $\pm$  9 /  $\pm$  17

Temperature stability (°C/°F)  $\pm 2 / \pm 4$ Subject to technical alterations and amendments.

### TECHNICAL DATA SOLDERING IRON WTPP MS

Temperature range °C 100 - 450 Temperature range °F 150 - 950

Power consumption (W) 40 W (55 W)

Mains supply voltage (V/Hz) 12V / AC

Heat-up time (50°C to 350°C) (120°F to 660°F) 3 sec.

Safety rest WSR 205

Tip type series RTP MS

Supply unit WT 1M, WT 2M, WR 3M

Subject to technical alterations and amendments.